

BS3000

INDUSTRIAL WIRED 1D CCD BARCODE SCANNER

EVERYCOM

The Everycom BS3000 1D CCD Barcode Scanner Rises Above Conventional Imagers To Deliver Unprecedented Scanning Performance On Virtually Every 1d Barcode, Keeping Your Checkout Lines Moving And Your Cashiers Free To Deliver A More Personal Checkout Experience. The BS3000 Series Because When It Comes To The Checkout Experience In Your Store, Only The Best Will Do. With This Unique Combination Of Hardware And Advanced Algorithms, The BS3000 Series Instantly Captures The Most Problematic Barcodes With Lightning Speed



Supports With Android, Windows, Mac & Linux OS.



Industrial Anti-Shock/Drop/Dust Design. CCD Sensor with Super Depth of Scan Field. 300scans/sec High speed scanning, 4mil High Resolution PS2 And RS232 as Optional Interface

Unrivalled Performance

An Industry-leading Two-year Warranty, Ensuring Reliable Performance Year After Year With No Downtime

Ease-of-use

True Point-and-shoot Handheld Ergonomics Easily Fits Oversized Gloved Hands, While Intuitive Aiming Means Operators Will Become Productive Quickly

Plug and play

No Driver Installation Required, Simply Plug And Play Across Supported Platforms.

SPECIFICATIONS

- Scan Speed : 300 Scans/sec
- 5-630mm Super Depth of Scan field.
- Can scan from the phone / computer and other electronic screens.
- Super Scanning And Decoding Ability, Can Read Incomplete And Fuzzy Codes.
- Supports Multi Keyboard Languages
- Anti-shock, Anti-drop & Anti-dust design. Suitable for all kind of Industrial Environment
- Application fields: Supermarket, Retail, Warehouse, Logistic, Library, Medical etc.
- Can be customized according to customer demand.



Hands-Free Intellistand
BS1000-HLD (Sold Separately)

BS3000

| Performance Parameters | |
|---------------------------------|--|
| Light Source | 620NM Visible Red Light Diode |
| Scan Speed | 300 Scans/sec |
| Scan Angle | ± 60 ° ± 65 ° ± 42 ° (left and right, front and rear, turn) |
| Depth of field | 5mm-630mm |
| Imaging Sensor | CCD |
| Resolution | 4mil |
| Light Levels | 3000-12000Lux |
| Minimum Print Contrast | 30% Minimum Reflectance Difference |
| Physical Characteristics | |
| Dimensions | 6.5 X 2.5 X 3.0 in (Approx) |
| Scanner Weight | 128 Grams |
| Package Weight (Incl. Scanner) | 280 Grams |
| Color | Black |
| Housing | ABS+Rubber |
| Charging Voltage Range | DC 5VDC ± 0.25 V |
| Supported Host Interfaces | USB (Optional PS2, RS232) |
| User Indicators | Buzzer, LED |
| User Environment | |
| Operating Temperature | -20°C to 50°C (Work):- 40°C to 60°C (Storage) |
| Humidity | 5% to 95% relative humidity, non condensing |
| Drop Specification | Designed To Withstand Multiple Drops At 3.0M To Concrete |
| Environmental Sealing | IP54 |
| Regulatory | |
| Electrical Safety | Certified to BIS IS13252(Part-1) / IEC60950-1, EN60950/IEC950 |
| EMI/RFI: | FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA, Taiwan EMC, Japan VCCI/MITI/Dentori |
| Environmental | Compliant with ROHS Directive 2002/95/EEC |
| Electrical | |
| Power | 250 mW (work): 500 mW (maximum instantaneous) |
| Current | 50 mA (work): 100 mA (maximum instantaneous) |
| Accessories | |
| Hands-Free Intellistand | BS1000-HLD (Sold Separately) |
| Package Content | |
| Package Content | 1x BS3000 Barcode Scanner , 1 x USB to RJ45 Cable , 1 x User Manual |